



HW specifications for Dell servers to run Norman Network Protection

Description	Quantity
210-19610 1 PE1950 III Quad-Core Xeon E5420 2.5GHz/2x6MB 1333FSB	
330-10062 PE1950 PCIE Riser (2 Slots)	1
340-13544 European - Documentation and Rack Power Cord	1
350-10163 PE1950 Bezel Assembly	1
370-12855 4GB FB 667MHz Memory (2x2GB dual rank DIMMs)	1
374-10366 No second Processor option	1
400-14441 73GB SAS (15,000rpm) 3.5 inch Hard Drive	2
404-10113 PE1950 III 3.5" HDD support chassis	1
405-10805 Perc 6i Integrated Controller	1
429-12417 8X IDE DVD-ROM Drive	1
450-11656 PE1950 III Redundant Power Supply - No Power Cord	1
450-10455 Power Cord, PDU (Rack)	1
540-10399 Broadcom NetXtreme II 5708 Single Port Gigabit NIC w/TOE, PCIe-4	1
541-10000 Broadcom TCP/IP Offload Engine functionality (TOE) Not Enabled	1
611-10036 No Operating System	1
631-10103 PE1950 OpenManage kit and FI Driver	1
683-11870 You have chosen not to take the Dell PowerEdge installation service	1
770-10635 Sliding Combination Rapid/Versa Rail with CMA	1
780-10915 PE1950 III - C3,MSSR1, ADD IN PERC 5i/6i or SAS6iR, min 2 / max 2	1
800-10508 PowerEdge Order - Norway	1
709-10036 Base Warranty	1
709-10037 1Yr Basic Warranty - Next Business Day	1
710-10506 3Yr ProSupport for IT and Next Business Day On-Site Service	1

OS for the servers

Both the OS and Norman Network Protection software are provided with the Norman Network Protection Installer ISO or CD. Contact your nearest Norman office or Norman dealer.

Do not install anything else on the hardware.